

Nomex® MHP

34% Nomex®, Kevlar®, 33% Lyocell, 31% Modacrylic, 2% Antistatic Fiber

CAUTION READ BEFORE USE

- 1) Flammable Contaminants will reduce the thermal protection of any flame resistant garment. For maximum protection:
 - Wash your new garment before wearing and after each subsequent wearing to thoroughly remove potentially flammable contaminants.
 - Wearing undergarments is recommended with all flame resistant garments.
 - It is the responsibility of the garment user to examine its condition before and after each use to be sure it is suitable for use.
- 2) Anti-static garments of Nomex® MHP should be used in conjunction with proper grounding procedures for maximum protection against the threat of spark. Do not remove garments in a hazardous environment.

GARMENT CARE

- For correct fit, try garment on before washing or wearing.
- Wash new garments before and after each wearing.
- Wash garments of Nomex® MHP separately from other garments.
- Wash light and dark colors separately.
- Launder this garment separately from non-flame resistant clothing.
- Wash dark and light colors separately.
- Secure all closures before washing and drying.
- Pretreat greasy stains.
- Machine wash in hot water (maximum 140 °F / 60 °C) with a commercially available detergent.
- Do not use chlorine bleach or detergents containing chlorine bleach.
- Tumble-dry on low heat (maximum 160 °F / 71 °C).
- Do not over-dry. Remove promptly.
- Do not use fabric softeners or dryer sheets.
- When using commercial laundry aids, be sure to read and carefully follow manufacturer's instructions.
- Removal of grease or oil stains may require dry cleaning.
- Do not store or line-dry in sunlight.